



| | SERIE ZV-POL 2-2354 | SERIE ZV-POL 2-2356 | SERIE ZV-POL 2-2357 | SERIE ZV-POL 2-2358 | SERIE ZV-POL 2-2359 |
|--------------------------------------|--------------------------------|--------------------------------|--------------------------------|--------------------------------|--------------------------------|
| Diámetro (mm) | 80 mm | 100 mm | 125 mm | 150 mm | 200 mm |
| Ancho de banda (mm) | 32 mm | 32 mm | 32 mm | 42 mm | 50 mm |
| Capacidad de carga (kg) | 100 kg | 150 kg | 200 kg | 250 kg | 300 kg |
| Cojinete | Liso | Liso | Liso | Liso | Liso |
| Medidas de la placa (mm) | 105x80 mm | 106x86 mm | 106x86 mm | 140x110 mm | 140x110 mm |
| Distancia entre agujeros (mm) | 86/80x60 mm | 86/80x60 mm | 86/80x60 mm | 105x80 mm | 105x80 mm |
| Altura total (mm) | 110 mm | 133 mm | 155 mm | 196 mm | 242 mm |
| Radio de giro (mm) | 77 mm | 95 mm | 107 mm | 128 mm | 153 mm |
| Diámetro agujero (mm) | 8 mm | 8 mm | 8 mm | 10 mm | 10 mm |
| Temperatura Mínima (°C) | -25 °C | -25 °C | -25 °C | -25 °C | -25 °C |
| Temperatura Máxima (°C) | +80 °C | +80 °C | +80 °C | +80 °C | +80 °C |