
Product name	:	MoTip Leak Detector	
Article number	:	090406	
Supplier / Producer	:	MOTIP DUPLI B.V.	
		Wolframweg 2	
		NL-8471 XC WOLVEGA	
		Telephone number	+31 561 – 69 44 00
		Telefax number	+31 561 – 69 44 31

Product description

High quality spray to trace leakages in gas pipes.

Applications

Compressors
Gas pipes
Air pipes
Tyres

Product characteristics

DVGW certified, number NG/5170BR0105
Non-flammable
Can be removed with water
Non-corrosive
Environment-friendly
Slightly foaming
Slightly basic
High yield

Physical and Chemical Characteristics

Contents	:	400 ml
Basis	:	Tenside solution
Propellant	:	Inert propellant
VOC-content	:	0% w/w
Colour	:	Transparent
Relative density at 20°C	:	1,02 g/ml
Yield	:	2,8 g/sec
Vapour pressure at 20°C	:	8 to 9 bar
Rest pressure	:	3,5 to 4,5 bar
Appearance	:	Foamy at leakage
pH-value	:	7 – 7,5



Usage

Before use, carefully read the directions on the packaging and act accordingly.
Store frost-free.

Best processing temperature 5 to 30°C.
Before use, shake the aerosol.

Apply leak detector to the suspected zone in order to trace the leakage.
Bubbles will appear at the place of the leakage.
Superfluous spray can be removed with water.