

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 70

Revision: 02.06.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: MOTIP CUT & DRILL LUBRICANT

· Article number: 090407

 \cdot 1.2 Relevant identified uses of the substance or mixture and uses advised against

- No further relevant information available.
- $\cdot \textit{Application of the substance / the mixture } Lubricant$

1.3 Details of the supplier of the safety data sheet
Manufacturer/Supplier: MOTIP DUPLI B.V. Wolfraamweg 2 NL- 8471 XC Wolvega The Netherlands Tel: +31 (0)561 694400 Fax: +31 (0)561 694411 e-mail info@nl.motipdupli.com

• Further information obtainable from: QHSE Department • 1.4 Emergency telephone number: +31 (0)561-694400 (09:00h - 17:00h)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008



Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC

F+; Extremely flammable

R12: Extremely flammable.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version. Warning! Pressurised container.

warning! Pressurisea containe

• Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· 2.2 Label elements

- · Labelling according to Regulation (EC) No 1272/2008
- *The product is classified and labelled according to the CLP regulation. Hazard pictograms*



Signal word Danger
 Hazard statements
 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

(Contd. on page 2)

GB

Page 2/7

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 70

Revision: 02.06.2015

(Contd. of page 1)

Trade name: MOTIP CUT & DRILL LUBRICANT

· Precautionary statements

Keep out of reach of children. P102

P260 Do not breathe spray.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P211 Do not spray on an open flame or other ignition source.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

Danaganana again an anta

	Mineral oil	25-50%
	🚸 Asp. Tox. 1, H304	
CAS: 64742-48-9 EC number: 918-481-9 Reg.nr.: 01-2119457273-39-xxxx	Naphta (petroleum), hydrotreated heavy Xn R65 R66-67 � Asp. Tox. 1, H304	12.5-20%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	propane F+ R12 Flam. Gas 1, H220 Press. Gas C, H280	12.5-20%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32-xxxx	butane F+ R12 Flam. Gas 1, H220 Press. Gas C, H280	5-10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27-xxxx	isobutane F+ R12 Flam. Gas 1, H220 Press. Gas C, H280	5-10%

• Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· After inhalation: Supply fresh air; consult doctor in case of complaints.

- After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

• After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

(Contd. on page 3)

Page 3/7

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 70

Revision: 02.06.2015

(Contd. of page 2)

Trade name: MOTIP CUT & DRILL LUBRICANT

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation Keep away from ignition sources.
- · 6.2 Environmental precautions:
- Do not allow product to reach sewage system or any water course.
- Inform respective authorities in case of seepage into water course or sewage system.
- Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling No special measures required.

Ensure good ventilation/exhaustion at the workplace.

- Information about fire and explosion protection:
- Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:
- Store in a cool location.
- Observe official regulations on storing packagings with pressurised containers.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane

WEL Short-term value: 1810 mg/m³, 750 ppm

Long-term value: 1450 mg/m³, 600 ppm

Carc (*if more than* 0.1% *of buta-1.3-diene*)

• Additional information: The lists valid during the making were used as basis.

(Contd. on page 4)

Page 4/7

*

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 70

Revision: 02.06.2015

(Contd. of page 3)

Trade name: MOTIP CUT & DRILL LUBRICANT

· 8.2 Exposure controls

· Personal protective equipment:

• General protective and hygienic measures: Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols.

- **Respiratory protection:** Not required.
- Protection of hands: Not required.
- Material of gloves Not required.
- Penetration time of glove material Not required.
- Eye protection: Not required.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties				
· General Information				
· Appearance:				
Form:	Aerosol			
Colour:	According to product specification			
• Odour:	Characteristic			
· Odour threshold:	Not determined.			
· pH-value:	Not determined.			
· Change in condition				
Melting point/Melting range:	Undetermined.			
Boiling point/Boiling range:	Not applicable, as aerosol.			
· Flash point:	$< 0 \ ^{\circ}C \ (< 32 \ ^{\circ}F)$			
-	Not applicable, as aerosol.			
· Flammability (solid, gaseous):	Not applicable.			
· Ignition temperature:	> 200 °C (> 392 °F)			
· Decomposition temperature:	Not determined.			
· Self-igniting:	Product is not selfigniting.			
• Danger of explosion:	Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.			
· Explosion limits:				
Lower:	0.6 Vol %			
Upper:	10.9 Vol %			
• Vapour pressure at 20 •C (68 •F):	3500 hPa (2625 mm Hg)			
• Density at 20 •C (68 •F):	0.735 g/cm ³ (6.134 lbs/gal)			
· Relative density	Not determined.			
· Vapour density	Not determined.			
· Evaporation rate	Not applicable.			
· Solubility in / Miscibility with				
water:	Not miscible or difficult to mix.			
· Partition coefficient (n-octanol/water	r): Not determined.			
· Viscosity:				
Dynamic:	Not determined.			
Kinematic:	Not determined.			
· Solvent content:				
Organic solvents:	50.0 %			
· EU-VOC:	367.5 g/l			
	(Contd. on page 5)			

Page 5/7

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 70

Revision: 02.06.2015

(Contd. of page 4)

Trade name: MOTIP CUT & DRILL LUBRICANT

• EU-VOC in %: • 9.2 Other information 50.00 % No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

• 10.3 Possibility of hazardous reactions No dangerous reactions known.

• 10.4 Conditions to avoid No further relevant information available.

 \cdot 10.5 Incompatible materials: No further relevant information available.

• 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity

· LD/LC50 values relevant for classification:

64742-48-9 Naphta (petroleum), hydrotreated heavy

Oral LD50 >15000 mg/kg (rat)

Dermal LD50 >3000 mg/kg (rab)

Inhalative LC50/4h >2.8 mg/m3 (rat)

106-97-8 butane

Inhalative LC50 / 4 h 658000 mg/m3 (rat)

· Primary irritant effect:

· Skin corrosion/irritation No irritant effect.

· Serious eye damage/irritation No irritating effect.

· Respiratory or skin sensitisation No sensitising effects known.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

64742-48-9 Naphta (petroleum), hydrotreated heavy

LC50 / 96 h >100 mg/l (crustacean (amphipod))

>100 mg/l (fish)

· 12.2 Persistence and degradability No further relevant information available.

· 12.3 Bioaccumulative potential No further relevant information available.

· 12.4 Mobility in soil No further relevant information available.

· Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· 12.5 Results of PBT and vPvB assessment

• *PBT:* Not applicable.

· **vPvB:** Not applicable.

· 12.6 Other adverse effects No further relevant information available.

(Contd. on page 6)

Page 6/7

*

*

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 70

Revision: 02.06.2015

Trade name: MOTIP CUT & DRILL LUBRICANT

(Contd. of page 5)

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

20 01 13* solvents

15 01 04 metallic packaging

· Uncleaned packaging:

· Recommendation: Non contaminated packagings may be recycled.

14 1 KINI Naamah an		
14.1 UN-Number ADR, IMDG, IATA	UN1950	
14.2 UN proper shipping name		
ADR	1950 AEROSOLS	
IMDG	AEROSOLS	
ΙΑΤΑ	AEROSOLS, flammable	
14.3 Transport hazard class(es)		
ADR		
Class	2 5F Gases.	
Label	2.1	
Class	2.1	
Label	2.1	
14.4 Packing group ADR, IMDG, IATA	Void	
14.5 Environmental hazards:		
Marine pollutant:	No	
14.6 Special precautions for user	Warning: Gases.	
Danger code (Kemler):	-	
EMS Number:	F- D , S - U	
14.7 Transport in bulk according to Anno MARPOL73/78 and the IBC Code	ex II of Not applicable.	
Transport/Additional information:		
ADR		
Limited quantities (LQ)	1L	
Excepted quantities (EQ)	Code: E0	
The second se	Not permitted as Excepted Quantity	
Transport category	2	

Page 7/7

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2015

Version number 70

Revision: 02.06.2015

Trade name: MOTIP CUT & DRILL LUBRICANT

		(Contd. of page 6)
· Tunnel restriction code	D	
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity	
· UN "Model Regulation":	UN1950, AEROSOLS, 2.1	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

- H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways.
- R12 Extremely flammable.
- *R65* Harmful: may cause lung damage if swallowed.
- *R66 Repeated exposure may cause skin dryness or cracking.*
- Vapours may cause drowsiness and dizziness. R67
- · Department issuing MSDS: R&D legislation and regulatory advisor
- · Contact: Mr. K. Smedeman
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- Flam. Gas 1: Flammable gases, Hazard Category 1 Flam. Aerosol 1: Flammable aerosols, Hazard Category 1
- Press. Gas C: Gases under pressure: Compressed gas
- Asp. Tox. 1: Aspiration hazard, Hazard Category 1
- $\cdot *$ Data compared to the previous version altered.

[·] Directive 2012/18/EU