



Issued to:

Kratos Safety SAS
689 Chemin Du Buclay
38540 Heyrieux
France

Notified Body: 2777

SATRA customer number: P0122

EU Type-Examination Certificate

Certificate number: 2777/10963-03/E14-01

This EU Type-Examination Certificate covers the following product group(s) supported by testing to the relevant standards/technical specifications and examination of the technical file documentation. It has been issued Under Module B of Regulation 2016/425 on personal protective equipment. This product group has been shown to satisfy the applicable essential health and safety requirements as a Category III product.

Product Reference

Description

FA 30 500 10
FA 30 500 15
FA 30 500 20

Energy absorbing rope lanyard. Consisting of 11mm diameter polyamide braided rope, with energy absorber attached, looped at either end with polyethylene thimble
Length of 1.0 metre
Length of 1.5 metres
Length of 1.8 metres

FA 30 502 10
FA 30 502 15
FA 30 502 20

Variant with steel scaffold hook at rope end
Length of 1.0 metre
Length of 1.5 metres
Length of 1.8 metres

FA 30 503 10
FA 30 503 15
FA 30 503 20

Variant with steel scaffold hook at rope end and steel snap hook at energy absorber end
Length of 1.0 metre
Length of 1.5 metres
Length of 1.8 metres

FA 30 512 12
FA 30 512 20
FA 30 513 20

Variant with aluminium scaffold hook at rope end
Length of 1.2 metres
Length of 2.0 metres
Length of 2.0 metres, variant with aluminium scaffold hook at one end and rebar hook at the energy absorber end, suitable for use with a maximum user mass of 140kg and use over an edge

FA 30 522 10
FA 30 522 12
FA 30 522 15
FA 30 522 20
FA 30 514 20

Variant with aluminium rebar hook at rope end and karabiner at energy absorber end.
Length of 1.0 metre, suitable for use with a maximum user mass of 140kg and use over an edge
Length of 1.2 metres, suitable for use with a maximum user mass of 140kg and use over an edge
Length of 1.5 metres, suitable for use with a maximum user mass of 140kg and use over an edge
Length of 2.0 metres, suitable for use with a maximum user mass of 140kg and use over an edge
Adjustable length of 1.5 to 2.0 metres, suitable for use with a maximum user mass of 140kg

Standards/Technical specifications applied:

EN 355:2002; VG11 RFU PPE-R/11.074; VG11 RFU PPE-R/11.062

Technical reports/Approval documents:

SATRA: 56772/0507/SPC-0/6, 21352/0120/SPC-0/2, 45392/0402, SPC0145091/0646, 58638/0516, 56722/0507, SPC0162839/0816/NW, 48332/0417/SPC-0/8, 171896/0906, SPC0171896/0906, SPC0173310/0913, SPC0189912/1047, SPC0162839/0816, SPC0201490/1207, SPC0289957/1938/2
DOLOMITICERT: 170241
CSA: 2682373

Signed on behalf of SATRA:

Geoff Graham

Date of issue: 09/08/2023
Expiry date: 16/06/2028

TERMS AND CONDITIONS

The following conditions apply in addition to SATRA's standard terms and conditions of business and those given in the current certification agreement. This certificate has been issued in accordance with Annex V (Module B) of the applicable legislation (see note 11).

Please note:

1. Where the product is classified as category III then CE or UKCA Marking of production is reliant on current compliance with module C2 or Module D of the applicable legislation (See note 11). (Except that specifically produced to fit an individual user).
2. Full details of the scope of the certification and product(s) certified are contained within the manufacturer's technical documentation.
3. Where a translation of this certificate exists, the English language version shall be considered as the authoritative text.
4. Certification is limited to production undertaken at the sites listed in the manufacturer's technical documentation.
5. Ongoing manufactured product shall be consistent with the product(s) certified and listed on this certificate and an EU declaration of product conformity shall be made available in accordance with the applicable legislation (See note 11)
6. The Manufacturer shall inform SATRA of any changes to the certified product or technical documentation.
7. Where results obtained during type testing are within the budget of uncertainty when compared to the pass requirement, classification or performance level, then it is the responsibility of the manufacturer to ensure that the factory production control and manufacturing tolerances are such that the product placed on the market meets with the stated requirements, classifications or performance levels.
8. This certificate shall be kept together with the relevant technical documentation in a safe place by the client named on this certificate. Production of this certificate and other documentation may be required by a representative of the EC member state, or UK government.
9. This certificate relates only to the condition of the testable items at the time of the certification procedure and is subject to the expiry date shown.
10. SATRA reserves the right to withdraw this certificate if it is found that a condition of manufacture, design, materials or packaging have been changed and therefore no longer comply with the requirements of the applicable legislation (See note 11).
11. These terms and conditions shall apply to the requirements set out in Regulation (EU) 2016/425 of the European Parliament and of the council of 9th March 2016 on personal protective equipment or to UK legislation relating to UKCA Marking as defined within the issued certificate.